



carmen
CERAMIC ART

Technical characteristics report

Serial: DORSET

Size: 60x60

Porcelain tiles

Norm: UNE-EN 14411

Group: Bla

Dorset Grey Mix(7) Rect. 60x60

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,2%
Flexion resistance	EN ISO 10545-04	> 50 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2.100 rev.)
Hardness degree, method MOHS	UNE 67-101-92	6
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	Class 1 (21)



carmen
CERAMIC ART

Technical characteristics report

Serial: DORSET

Size: 60x60

Porcelain tiles

Norm: UNE-EN 14411

Group: Bla

Dorset Cream Mix(7) Rect. 60x60

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,2%
Flexion resistance	EN ISO 10545-04	> 50 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (6.000 rev.)
Hardness degree, method MOHS	UNE 67-101-92	6
Thermal shock resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GLA
Resistance to cleaning products	EN ISO 10545-13	GA
Resistance to chemical products to swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5
Slip resistance (Rd)	UNE-ENV 12633:2003	Class 1 (21)

QUALITY DEPARTMENT